



BOXY 2 L 92733 DIM8 B-B

10727 9228 B-B

AVAILABLE IN



SCHWARZ-SCHWARZ 10727 9228 B-B

SCHWARZ-FLEMISH BRONZE 10727 9228 B-FBR

SCHWARZ-FLEMISH GOLD 10727 9228 B-FG

SCHWARZ-VERGOLDET MAT 10727 9228 B-MMAT

WEISS-WEISS 10727 9228 W-W



[View on website](#)

General info	
LOCATION	innenbereich
INSTALLATION	Decke Aufbau
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	nicht verstellbar
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC >> B-MMAT only interior use - other colours also exterior use

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	Phasenabschnitt
ENERGY CLASS	E
CERTIFICATION	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 7,1W / CRI>90 (R9: 60) / 2700K / 779lm)
RVALUES	Rf: 89 / Rg: 100
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1558lm // 14,2W // 110lm/W
LED TECHNICS (LUMINAIRE)	1243lm // 16W // 76lm/W

Accessories	
BOXY HONEYCOMB	
BOXY SOFTENING LENS	
BOXY GLASS SBL	


BOXY 2 L 92733 DIM8 B-B

10727 9228 B-B

For detailed installation instructions, please consult the manual: [10727_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Vorschaltgeräte und Trafos



300 90 004 ED8 WIRELESS CONTROL DIM8

Licht veredelndes Zubehör



Ø40



Ø45
1.5

251 70 03 01 B BOXY HONEYCOMB B

251 70 03 01 W BOXY HONEYCOMB W



Ø40



Ø45
1.5

251 70 03 04 B BOXY SOFTENING LENS B

251 70 03 04 W BOXY SOFTENING LENS W



Ø40



Ø45
1.5

251 70 03 05 B BOXY GLASS SBL B

251 70 03 05 W BOXY GLASS SBL W



BOXY 2 L 92733 DIM8 B-B

10727 9228 B-B

Notes: