


las.2



Lichttechnik:
230V Power LED
2700K
L70/50.000 h

dimmbar über Phasenabschrittdimmer
optional mit integriertem DALI-2-Phasendimmer

Installation:
2x Kabeleinführung; Anschlussklemme 3x 2,5 mm²

Material:
Aluminiumguss pulverbeschichtet
+ pure white: Klarglas . deep black: rauchfarbenes Glas

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle
der Energieeffizienzklasse G

Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

dimmbable via trailing edge dimmer
with integrated DALI-2 phase dimmer as an option

installation:
2x cable entry point; connection terminal 3x 2,5 mm²



material:
aluminium die-casting powder-coated
+ pure white: clear glass . deep black: smoked glass

protection class: IP65

This product contains a light source of
energy efficiency class G

light direction:



Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 deep black RAL 9005	93155-BL 93155-BL-DR . DALI-2 ready	6 W/115 lm
 pure white RAL 9016	93155-WH 93155-WH-DR . DALI-2 ready	6 W/250 lm

Größe in mm
size in mm