



lix spike solar join Design: Klaus Nolting

für unbefestigte Beet- und Grünflächen for unpaved beds and greens

Lichttechnik:
LED
Lithium-Ionen Akku
1x 2600 mAh
2700K

Betriebsdauer:
automat. Einschaltung bei Dämmerung für die Dauer von etwa 5 Std.

Anschluss:
0,8 m Zuleitung (H05RN8-F 2x0,75 mm²) inkl. solar join Stecker

ortsveränderlich

Material:
Aluminiumguss pulverbeschichtet + Polycarbonat matt

Schutzart:
IP65



Lichtrichtung:



light technology:
LED
lithium-ion battery
1x 2600 mAh
2700K

operating time:
automatic switch-on at dusk for a duration of approx. 5 hrs.

connection:
0,8 m supply cable (H05RN8-F 2x0,75 mm²) incl. solar join plug


movable

material:
aluminium die-casting powder-coated + polycarbonate matt

protection class:
IP65



light direction:




Größe in mm
size in mm

Farbe colour	Art.-Nr. item no.	Systemleistung system performance
anthracite RAL 7016	93093-AN-JO	4,4 W/260 lm 1x lix spike solar join - 1,1 W/65 lm 4x lix spike solar join
cool brown	93093-CB-JO	4,4 W/260 lm 1x lix spike solar join - 1,1 W/65 lm 4x lix spike solar join
deep black RAL 9005	93093-BL-JO	4,4 W/260 lm 1x lix spike solar join - 1,1 W/65 lm 4x lix spike solar join

IP44.DE solar join Zubehör accessory




Erforderliches Zubehör required accessory

solar panel L




Größe in mm
size in mm

Solarpanel
Lithium-Ionen Akku
4x 2600 mAh
1 m Zuleitung (H05RN8-F 2x0,75 mm²)
Schutzart: IP65
solar panel
lithium-ion battery
4x 2600 mAh
1 m supply cable (H05RN8-F 2x0,75 mm²)
protection class: IP65

Farbe colour	Art.-Nr. item no.
 anthracite RAL 7016	53110-AN
 cool brown	53110-CB
 deep black RAL 9005	53110-BL


Optionales Zubehör optional accessory



Verlängerungskabel
extension cable

solar join Stecker auf solar join Buchse
Kabel: H05RN8-F 2x0,75 mm²
Schutzart: IP68
solar join plug on solar join socket
cable: H05RN8-F 2x0,75 mm²
protection class: IP68

2 m	53102
4 m	53104
8 m	53108



Verteiler
junction

1x solar join Stecker; 2x/3x/4x solar join Buchse
Kabel: H05RN8-F 2x0,75 mm²
Schutzart: IP68
1x solar join plug; 2x/3x/4x solar join socket
cable: H05RN8-F 2x0,75 mm²
protection class: IP68

port 2	53122
port 3	53123
port 4	53124