




iem.2 X



Lichttechnik:
230V Power LED
2700K
L70/50.000 h

Reflektor: schwarz

dimmbar über Phasenabschrittdimmer
optional mit integriertem DALI-2-Phasendimmer

Installation:
2x Kabeleinführung; Anschlussklemme 3x 2,5 mm²

Material:
Aluminiumguss pulverbeschichtet
+ Sicherheitsglas klar

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle
der Energieeffizienzklasse G

coastal grade finish

Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

reflector: black

dimmable via trailing edge dimmer
with integrated DALI-2 phase dimmer as an option

installation:
2x cable entry point; connection terminal 3x 2,5 mm²

material:
aluminium die-casting powder-coated
+ safety glass clear

protection class: IP65

This product contains a light source of
energy efficiency class G

coastal grade finish

light direction:



Farbe
colour



anthracite
RAL 7016

Art.-Nr.
item no.

92284-AN
92284-AN-DR . DALI-2 ready

Systemleistung
system performance

16 W/820 lm



cool brown

92284-CB
92284-CB-DR . DALI-2 ready

16 W/820 lm



deep black
RAL 9005

92284-BL
92284-BL-DR . DALI-2 ready

16 W/820 lm

+ verwandte Produkte related products . iem.2 X down

Größe in mm
size in mm